

DSA Dry Spray Equipment



Use to add materials such as ATH to gel coat for spray granite. This unit will also spray micro spheres for a smooth sandable surface. These units can be attached to most resin/gell coat spray-up machines. Heavy duty container will give years of service. Pneumatic activation assembly can be signaled from the chopper port on most machines. 25ft. of reinforced hose and activation line supplied.

DSA-150-V25C



- * PolyPro vacuum valve assembly to reduce condensation
- * Large Diameter $\frac{3}{4}$ ID reinforced hose.
- * Complete w/4 way valve activation and slide valve trigger
- * Unique graduated, color coded needle valve for accurate air control and material volume.
- * 15 gallon graduated HDPE tank included screw w/vented lid.
- * Standard 25ft. reinforced material hose.
- * 25ft. low volume LPDE activation hose included.



Shown here w/GlasCraft AAC

- * DSA's use a simple, efficient venture valve assembly for consistent granite and flake patterns.
- * All DSA's use a strong aluminum base for stable mounting with any spray up machine.
- * Unique to ES Mfg. is our low pressure vacuum generator that causes no disturbance in gel coat pattern.
- * Loc-Line adjustable nozzle with 1-1/4" flare fitting.
- * Separate rotary vibrator to improve dry spay consistency.